

广州中逸光电子科技有限公司

测试报告 (Inspection report)

产品型号: ZP12-S12				批号:				日期: 2017-9-20				仪器编号: LW2676;ADS1062C			
1. 耐压测试															
Input to Output <u>4000</u> VAC Leakage current <u>0.63</u> mA at 1 min OK!															
2. 测试数据															
输入				输出											
U _{in} (VAc)		I _{in} (A)	P _{in}	U _{out} (V)		I _{out} (A)	P _{out}	效率	纹波噪声 (mV)	电压精度	电压调整率	负载调整率			
100	最小载	0.025	1.57	11.946		0.100	1.195	76.09%	20	-0.57%	0.05%	0.08%			
	半载	0.102	7.44	11.944		0.500	5.972	80.27%	40						
	满载	0.225	15.30	11.936		1.000	11.936	78.01%	50						
140	最小载	0.022	1.62	11.947		0.100	1.195	73.75%	20						
	半载	0.079	7.40	11.945		0.500	5.973	80.71%	30						
	满载	0.159	15.00	11.938		1.000	11.938	79.59%	65						
240	最小载	0.015	1.74	11.947		0.100	1.195	68.66%	20						
	半载	0.057	7.55	11.942		0.500	5.971	79.09%	40						
	满载	0.099	14.80	11.932		1.000	11.932	80.62%	50						
										测试结果	符合技术手册参数要求 pass				
3. 稳定性															
Vout	0%-100%load			OK		启动模式	turn on		OK		测试结果	符合技术手册参数要求 pass			

测试	陆华香 2017-9-20	批准	姚桂花2017-9-20
----	---------------	----	--------------